

Mobridge Compact Class Rules 2023

Compact Class rules (Single Heat) General:

1. Entry is \$50.00
2. All cars must be equipped with seat belts for the driver.
3. Cars must have a wheelbase of 107.5" or smaller. All wheel drive cars must remove driveshaft to make 2-wheel drive.
4. Only driver shall be allowed in arena after the derby as started.
5. All drivers must remain in their car after their car is eliminated until the contest is over. Driver may exit car during fire or removal of debris from derby arena. Helmet and seatbelt must remain on.
6. It is illegal to hit driver's door. Anyone doing so will be called out. Also, no blocking with the driver's door.
7. All contestants must sign a waiver before participating in the derby.
8. After second fire, car is eliminated.
9. One-minute contact rule. Any car not moving and making contact for one minute will be eliminated.
10. No sandbagging or holding! You will be disqualified.
11. Top three cars WILL be re-inspected before any prize money is handed out.
12. Only the last two cars running will be pulled apart to determine places.
13. Any controversies will be taken up at the driver's meeting.
14. No profanity of any kind on cars or roof signs. This is a family show. You will have to paint or cover it up or you will not run.
15. JUDGES DECISIONS ARE FINAL!! There will be no arguing on or off the track or the authorities will escort you off the premise at that time.
16. No hot-rodding in the pits. Keep it at an idle.
17. Driver's meeting is MANDATORY.
18. All cars MUST be teched by 4:00 pm. THE EARLIER THE BETTER!

CAR PREPARATION:

1. All glass MUST be removed from the car. No exceptions.
2. Original gas tank must be removed. Replacement tank cannot be plastic. You must use a metal boat tank or well-made fuel cell and it must be properly secured (No tarp straps or zip ties).
3. Exhaust system must be removed and modified.
4. All loose chrome, plastic, fiberglass header, door handles, door locks, and wheel weights must be removed. Anything that will fall off must be removed.
5. Inside the car must have all flammable material (carpet, headliner, rear seat, etc.) removed. Driver-side panel may be left in for protection, or foam padding can be added.
6. Batteries must be removed from the engine compartment and securely mounted and covered inside the car.
7. Gas lines must be modified and safely run through the car.
8. A-arms, ball joints, and tie rods must remain stock.
9. All trailer hitches and braces must be removed.
10. Transmission cooler lines inside of the car should be covered.
11. No additional reinforcing of the car is allowed unless specified in the rules.

12. Radiator must be in stock location and no reinforcing of radiator support. No radi-barrels, no water barrels.
13. Any tire will be allowed, must be air filled. No larger and 16” tires. No larger than 7” wheel centers are allowed. No bead protection. No bead lockers. May have valve stem protectors.
14. Engines must be 6 cylinder or less. Rotary engines are ok. No alcohol running motors.
15. Car MUST have functioning brakes.
16. Any 5 lug rear-end in any car with stock axles only. No full floater rear-ends. No braces, must mount the same as per factory for the vehicle it is in. Must have stock trailing arms.
17. No bottles, cans, or any garbage in trunk or floors of cars.
18. Cars will be checked at inspection.

BODY:

1. Doors may be chained in six locations per door, seam between front and rear doors counts as 1 for each door or you may weld two 4x4x1/8 plates on vertical seam only. Driver door may be welded solid or safety.
2. No body shaping allowed.
3. No 9 wire or chain in areas other than specified.
4. Fenders can have 5 bolts per fender on wheel wells.
5. Body mounts and spot welds much remain stock.

CAGE:

1. Cage may be no larger than 4” material and must be free floating. May have dash bar, door bar. Can connect them on each side of one bar, but may not be in front of dash bar, or extend 6” beyond rear of door bar. No tubes connecting to the floor other than halo bar. Halo may be welded to sheet metal only, NOT FRAME.
2. Gas tank mount/protector and only be 24” wide and must be 4” off the highest point of the floor underneath of it, 6” from the rear firewall.
3. May have 2 windshield bars, 1 rear “window bar”. No bars can go more than 3” past window seam. No bars bigger than 2x2 OD or 2” round OD.

FUEL TANK:

1. Original gas tanks must be removed. You must use a boat tank or well-made fuel cell (11-gallon max) and it must be properly secured (no ratchet straps or bungees to hold the tank in place). No gas cans. Place fuel tank behind driver’s seat or in the center of the car where the back seat used to be. Tank must be bolted to body sheet metal only (not to the frame) if bolted to the floor.

FRAME:

1. No frame welding allowed.
2. No frame shaping, tilting, tipping or pitching.
3. If caught with any frame infractions: Squaring, Pinning, Plating, Shrinking, Extra Seam Welding, Gussets, Etc. or anything else you can think of not outlined in the rules will have no chance to fix. You will be automatically loaded with no refunds! No unauthorized frame repairs allowed.
4. No rust repair on frames allowed.

HOODS and TRUNKS:

1. Hoods must have access for fires to be extinguished. Front hood pins may be welded to top of frame only and core support. Hood may be attached in six (Not including hinges) with max of 1" all thread. Hood pins may attach to sheet metal only unless otherwise stated.
2. Trunk lids may be cut or folded. May secure with 4 plates of 4x4 by 1/8", 4 chains, or 4 locations of 9 wire.

STEERING:

1. You may alter your steering column to prevent loss of steering. Steering knuckles, homemade steering shafts, etc.

SUSPENSION:

1. No reinforcing or altering of suspension allowed.
2. All cars may run 1 chain, 9 wire, cable per side around rearend and frame humps.
3. No added leafs or front coils in rear. Double rear coils are allowed.
4. Upper A-arm may be welded to frame with two 2x6x1/4" plates. Nothing can be welded to the lower control arm.

ENGINE MOUNTING:

1. Any motor can go in any make car but must be in stock location. Motor mounts must be as close to stock as possible (No adding additional supports).
2. Motor and transmission can be securely mounted, but do not strengthen the frame.
3. May use 2 3/8" chains or 1" X1/8" strap to secure motor.
4. No transmission brace, skid plate or plated pans allowed.

BUMPERS:

1. No stuffing or plating bumpers.
2. Hard nosing bumpers is ok with no added metal.
3. Any factory bumper on any car.
4. May seam weld skins.
5. Bumper can be welded to shock, shocks welded to frame. No extending shocks. May use 1/4" X3" plate 10 inches long instead of shocks on top of frame only.
6. No homemade/Manufactured bumpers.

MISCELLANEOUS:

1. Rumble seat in wagons can NOT be welded – Must be removed.
2. Do not tie front and back frames together on Uni-body cars.
3. All cars must be stock unless modification is stated in the rules.
4. Sliders are allowed if so desired.

If it is not in the rules, it does not mean that you can do it!

Call Cody Zeller @ (605)848-4891 if you have questions.